



Legend Uniform

Semi-automatic, uniform case sealer

Maximizes Productivity

Seals uniform cases with a belt speed of up to 24.4 meter (80') per minute

Simplifies Maintenance

Operator friendly self tensioning belt systems require no manual adjustments and reduce wear

Production Versatility

Features offset tape heads which allow for a minimum case height of 6.67 cm (2 5/8")

Robust Design

7 Gauge steel mast and 12 Gauge welded steel head and structural platform

Legend Uniform Semi-automatic, uniform case sealer

The Legend Uniform is an operator fed, semi-automatic, uniform, industrial grade case sealer designed to top and bottom seal corrugated cases. The Legend Uniform features offset tape heads which allow for a minimum case height of 6.67 cm (2 5/8").

Features and benefits

■ Performance

- Operator friendly self tensioning belt systems require no manual adjustments and reduce wear.
- Continuous belt drive speed of 80' per minute

■ Versatility

- Compact footprint
- Expansive case range
- Quick changeover
- Converts from 50 mm (2") to 76 mm (3") tape in the field
- Height adjustment with counter balanced flat spring with slide and lock mechanism
- Width adjustment has self-centering, interlocked guide rails with steel lock knob

■ Durability


- Ideal for 24/7 operations
- Powerful 1/3 HP high efficiency motor drive system
- 7 gauge steel mast & stainless steel side rails
- 12 gauge welded steel head and structural platform

■ Safety

- Single mast design allows operator clear path in machine
- Tape cartridge features patented locking knife guard

Optional equipment

- Top squeezers
- Pack tables
- Casters
- Top three flap folder
- Increased conveyor height
- 34" high case capability (type II)
- Mirror Image
- Jet Printer Adapter
- 3 phase electrics
- Spare parts kit
- 76 mm (3") wide PST (top & bottom)
- Spare cartridge
- Secondary stop button
- NEMA 12 electrical package
- NEMA 4 wiring-enclosure & switch



CaseLocker™ 60 series tape cartridges

- Patented locking knife guard system allows the blade to be exposed only when the rollers are depressed
- Telescoping tape core allows for varying tape core sizes
- Patented tool-less removal of blades and wipe rollers
- Processes weak corrugated
- No lubrication points
- Utilizes link bar and knife arm bearings for added strength

The company reserves the right to make technical alterations without prior notification.
© 2019 Signode Industrial Group, LLC / SIG 58 Rev 200319 / www.Signode.com



Legend Uniform Technical Specifications

Power	115VAC, single phase, 60 cycle Other voltages available Contact Loveshaw for details
Air	NA
Operating Speed	Continuous belt drive; 80' per minute (24.4/min.) - production rate depends on box size and operator dexterity
Case Range	Length: 114 mm (4-1/2 in) - infinite Width: 114 mm (4-1/2 in)- 508 mm (20 in) Height: 64 mm (2-5/8 in) - 610 mm (24 in)
Machine Dimensions	Length: 141 cm (55 5/16") Width: 94.77 cm (30 3/16") Height: 160.50 cm (61 3/16")
Weight	104 kg. (230 lbs.), uncrated
Conveyor Height	56.52 cm - 76.84 cm (22 1/4" to 30 1/4") Standard
3-2-1 Limited Warranty	3 Year - Tape Cartridges 2 Year - Complete drive system, motor/gear reducer 1 Year - All other parts except for wear and moving parts
Closure Material	Pressure sensitive tape

 **SIGNODE**
Loveshaw/Little David
1-800-572-3434
marketing@loveshaw.com